

trilux

PROFESSIONAL LED LIGHTING

LED GUIDE
liniLED®

liniLED®

1 liniLED®

Choose the number of meters



- Dimensions: H6xW12mm
- Minimum order: 1m
- Spool length 50m
- Max. connection length 20m
- Section length: 20cm

liniLED® Warm White
011601



liniLED® White
011607



liniLED® Blue
011606



liniLED® Green
011605



liniLED® Red
011604



liniLED® Amber
011603



2 Connecting

Choose your connection products



- Connector set 1m from strip to power supply **011786**
- Connector set 5m from strip to power supply **011788**



Inline connector to connect strips **011790**



Extension cord to connect strips with 26cm cable in between **011792**



End cap to protect end of strip Enclosed with connector set **011503**



Cast joint IP68 necessary for all outdoor applications **011533**

3 Fixing

Choose your fixing products



U-profile 1m with double sided tape **011369**



Saddle approximately 5 per meter **011375**

Line profile 20mm 1m **010982**

Acrylic 20mm frosted 1m **010959**

Acrylic 20mm clear 1m **010965**

End cap 20mm 2x **010969**

Mounting clip 20mm 3x **010977**


Line profile 40mm 1m **010985**

Acrylic 40mm frosted 1m **010961**

Acrylic 40mm clear 1m **010967**

End cap 40mm 2x **010971**

Mounting clip 40mm 3x **010979**



Wall profile indirect 1m **012807**


PC Cover profile 1m **011591**

End cap (l) **011571** (r) **011573**



Stair profile Silver 1m **011565**

Stair profile Black 1m **011567**



Stair profile indirect

Silver 1m **011836**

Stair profile indirect

Black 1m **011837**



Wall-/floorprofile Silver 1m **011593**

Wall-/floorprofile Black 1m **011595**


See catalogue for other lengths

4 Powering

Choose your power supply

Formula:

length (m) x 3,5W x 1.1 = ...W



Option 1

011305 | 25W | 6m

011309 | 40W | 10m

011313 | 60W | 15m

011319 | 100W | 25m

011327 | 150W | 38m

011331 | 200W | 52m

011335 | 320W | 83m

011339 | 500W | 129m



Option 2 (IP64)

011307 | 30W | 7m

011315 | 60W | 15m

011321 | 100W | 25m



Option 3 Power supply unit (IP66)

011850 | 120W | 31m

011851 | 240W | 62m

011852 | 480W | 124m

5 Controlling

Choose your controllers/dimmers



Option 1

Dimmer built-in/on **011455** | 80m

Digital dimmer with push button **011457** | 68m



Option 2

Dim/Controller **011147** | 135m



Option 3

Dim/Controller 12A

(0-10V/DMX) **011149** | 80m



Option 4

Dim/Controller basic

011150 | 60m



In combination with

wall panel **011466**



Option 5

Dim/Controller unit (IP66)

011853 | 120W | 34m

011854 | 240W | 68m

011855 | 480W | 137m

1 liniLED® RGB

Choose the number of meters



- Dimensions: H6xW12mm
- Minimum order: 1m
- Spool length 50m
- Max. connection length 10m
- Section length: 20cm

liniLED® RGB
011602



2 Connecting

Choose your connection products



- Connector set 1m from strip to RGB Controller [011745](#)
- Connector set 5m from strip to RGB Controller [011746](#)



Inline connector to connect strips [011747](#)



Extension cord to connect strips with 26cm cable in between [011748](#)



End cap to protect end of strip
Enclosed with connector set [011503](#)



Cast joint IP68 necessary for all outdoor applications [011533](#)

3 Fixing

Choose your fixing products



U-profile 1m with double sided tape [011369](#)



Saddle approximately 5 per meter [011375](#)



Line profile 20mm 1m [010982](#)

Acrylic 20mm frosted 1m [010959](#)

Acrylic 20mm clear 1m [010965](#)

End cap 20mm 2x [010969](#)

Mounting clip 20mm 3x [010977](#)




Line profile 40mm 1m [010985](#)

Acrylic 40mm frosted 1m [010961](#)

Acrylic 40mm clear 1m [010967](#)

End cap 40mm 2x [010971](#)

Mounting clip 40mm 3x [010979](#)



Wall profile indirect 1m [012807](#)


PC Cover profile 1m [011591](#)

End cap (l) [011571](#) (r) [011573](#)



Stair profile Silver 1m [011565](#)

Stair profile Black 1m [011567](#)



Stair profile indirect

Silver 1m [011836](#)

Stair profile indirect

Black 1m [011837](#)



Wall-/floorprofile Silver 1m [011593](#)

Wall-/floorprofile Black 1m [011595](#)


See catalogue for other lengths

4 Powering

Choose your power supply

Formula:

length (m) x 6W x 1.1 = ...W



Option 1

[011305](#) | 25W | 3m

[011309](#) | 40W | 6m

[011313](#) | 60W | 9m

[011319](#) | 100W | 15m

[011327](#) | 150W | 22m

[011331](#) | 200W | 30m

[011335](#) | 320W | 48m

[011339](#) | 500W | 75m



Option 2 (IP64)

[011307](#) | 30W | 4m

[011315](#) | 60W | 9m

[011321](#) | 100W | 15m

5 Controlling

Choose your controllers/dimmers



Option 1

RGB/Dim Controller [011147](#) | 80m



Option 2

RGB/Dim Controller 12A
(0-10V/DMX) [011149](#) | 36m



Option 3

RGB/Dim Controller basic
[011150](#) | 35m



In combination with wall panel [011466](#)



Option 4

RGB Controller Stand Alone
[011810](#) | 18m



Option 5

RGB/Dim Controller unit (IP66)

[011853](#) | 120W | 18m

[011854](#) | 240W | 36m

[011855](#) | 480W | 72m


liniLED® Side


1 liniLED® Side


Choose the number of meters





- Dimensions: H12xW12mm
- Minimum order: 1m
- Spool length 50m
- Max. connection length 20m
- Section length: 20cm


liniLED® Side Warm White 
011766

liniLED® Side White 
011765

liniLED® Side Blue 
011764

liniLED® Side Green 
011763

liniLED® Side Red 
011762

liniLED® Side Amber 
011761

2 Connecting

Choose your connection products



- Connector set 1m from strip to power supply 011767
- Connector set 5m from strip to power supply 011768



Inline connector to connect strips 011769



Extension cord to connect strips with 26cm cable in between 011770



End cap to protect end of strip Enclosed with connector set 011504

3 Fixing

Choose your fixing products



U-profile 1m with double sided tape 011369



Saddle approximately 5 per meter 011375


See catalogue for our wide range of aluminium profiles

4 Powering

Choose your power supply

Formula:

length (m) x 3,5W x 1.1 = ...W



Option 1

011305	25W	6m
011309	40W	10m
011313	60W	15m
011319	100W	25m
011327	150W	38m
011331	200W	52m
011335	320W	83m
011339	500W	129m

Option 2 (IP64)

011307	30W	7m
011315	60W	15m
011321	100W	25m

Option 3 Power supply unit (IP66)

011850	120W	31m
011851	240W	62m
011852	480W	124m

5 Controlling

Choose your controllers/dimmers



Option 1

Dimmer built-in/on 011455 | 80m
Digital dimmer with push button 011457 | 68m



Option 2

Dim/Controller 011147 | 135m



Option 3

Dim/Controller 12A (0-10V/DMX) 011149 | 80m



Option 4

Dim/Controller basic 011150 | 60m



In combination with wall panel 011466



Option 5

Dim/Controller unit (IP66)
011853 | 120W | 34m
011854 | 240W | 68m
011855 | 480W | 137m

liniLED® Side RGB

1 liniLED® Side RGB

Choose the number of meters



- Dimensions: H12xW12mm
- Minimum order: 1m
- Spool length 50m
- Max. connection length 10m
- Section length: 20cm

liniLED® Side RGB
011760



2 Connecting

Choose your connection products



- Connector set 1m from strip to RGB Controller [011771](#)
- Connector set 5m from strip to RGB Controller [011772](#)



Inline connector to connect strips [011773](#)



Extension cord to connect strips with 26cm cable in between [011774](#)



End cap to protect end of strip
Enclosed with connector set [011504](#)

3 Fixing

Choose your fixing products



U-profile 1m with double sided tape [011369](#)




Saddle approximately 5 per meter [011375](#)

See catalogue for our wide range of aluminium profiles

4 Powering

Choose your power supply

Formula:
length (m) x 6W x 1.1 = ...W



Option 1

011305	25W	3m
011309	40W	6m
011313	60W	9m
011319	100W	15m
011327	150W	22m
011331	200W	30m
011335	320W	48m
011339	500W	75m



Option 2 (IP64)

011307	30W	4m
011315	60W	9m
011321	100W	15m

5 Controlling

Choose your controllers/dimmers



Option 1

RGB/Dim Controller [011147](#) | 80m



Option 2

RGB/Dim Controller 12A
(0-10V/DMX) [011149](#) | 36m



Option 3

RGB/Dim Controller basic
[011150](#) | 35m



In combination with wall panel [011466](#)



Option 4

RGB Controller Stand Alone
[011810](#) | 18m



Option 5

011853	120W	18m
011854	240W	36m
011855	480W	72m



PROFESSIONAL LED LIGHTING



Triolight BV
Hermesweg 23-25
3771 ND Barneveld
The Netherlands

T +31 (0)342 450 506
F +31 (0)342 450 232
info@triolight.com
www.triolight.com